

AVS-B2120-2.8

1.4 Megapixel 720P Water-proof HDAVS IR-Bullet Camera



Features

- 1/3" 1.4Megapixel CMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- DWDR, Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 2.8mm fixed lens
- Max. IR LEDs length: 90'/30m, Smart IR
- IP67, DC12V

AVS-B2120-2.8

Specifications

Model	AVS-B2120-2.8
Camera	
Image Sensor	1/3" 1.4Megapixel CMOS
Effective Pixels	1305(H)×1049(V)
Electronic Shutter	1/3s ~ 1/100,000s
Frame Rate	30/60fps@720P
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2 (AGC On); 0Lux-IR LEDs on
Video Output	1-channel BNC HDAVS high definition video output / CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	90'/30m, Smart IR
Day/Night	Auto (ICR) / Color / B/W
Noise Reduction	2D / 3D
OSD Menu	Support
Lens	
Focal Length	2.8 mm
Angle of View	H: 91.6°
Mount Type	M12
General	
Power Supply	DC12V±20%
Power Consumption	Max 4.7W
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C; < 95% RH (no condensation)
Transmission Distance	Over 2625'/800m via 75-3 coaxial cable
Ingress Protection	IP67
Dimensions	Φ2.8"×6.5"/Φ70mm×165mm
Weight	0.77lb/350g
Material	Metal