

AVS-B2200

2 Megapixel 1080P Weather-proof IR HD-AVS Camera

- 1/3" 2Megapixel CMOS
- 25/30fps@1080P, 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- 3.6mm fixed lens
- Max. IR LEDs length 100', Smart IR
- IP66, DC12V

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

AVS-B2200

2 Megapixel 1080P Weather-proof IR HD-AVS Camera

Model	AVSB2200
Camera	
Image Sensor	1/3" 2Megapixel CMOS
Effective Pixels	1920(H)x1080(V)
Electronic Shutter	1/3s~1/100,000s
Video Frame Rate	1920x1080@25 fps ; 1920x1080@30 fps ; 1280x720@25 fps ; 1280x720@30 fps ; 1280x720@50 fps ; 1280x720@60 fps
Synchronization	Internal
Min. Illumination	0.05Lux@F1.2(0Lux IR LED on)
Video Output	1-channel BNC HD-AVS high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	100', Smart IR
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	3D/2D
OSD Menu	Support
Lens	
Focal length	3.6mm
General	
Power Supply	DC12V±10%
Power Consumption	Max 6.5W
Working Environment	-14°F - 122° F (-25°C - 50° C) 90% RH
Transmission Distance	Over 984' via 75-3 coaxial cable
Ingress Protection	Ingress Protection
Dimensions(WxDxH)	7.88"x3.5"x6.34" - 200.2mmx89.1mmx161.2mm
Weight	1.28lb - 580g