

ELIP-3000N

2 Megapixel Indoor/Outdoor, Full-Size Bullet IR Network Camera (Motorized Zoom)

When your project requires a workhorse camera, ELIP-3000N bullet camera fits the bill. The camera uses a 2 Megapixel SONY Exmor progressive scan CMOS which delivers amazing detail and color for both day and night.

150 ft. of nighttime infrared illumination means long range visibility in zero light. With 5mm-60mm motorized vari-focal lens and auto smart focus this camera is extremely versatile and will work for everything from a large commercial building to a local restaurant.

Additional features include Wide Dynamic Range, Auto White Balance, and Digital Noise Reduction. The camera also features a sturdy vandal rated housing, ONVIF compatibility, and a built-in mini SD card.



FEATURES

- 2 Megapixel SONY Exmor progressive scan CMOS
- Max 30fps @ 1920 × 1080
- ONVIF
- Smart Focus Function
- 5~60mm Motorized Megapixel Lens
- 150' IR Beam Distance

Revision: 1.5; November 2016

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com



SPECIFICATIONS

Camera

Image Sensor	2.0 Megapixel 1/2.8" Sony progressive scan CMOS
Total Pixels	1952 (H) × 1116 (V)
Effective Pixels	1944 (H) × 1104 (V)
S/N Ratio	50dB
Synchronization	Internal

Features

Min. Illumination	0 Lux (IR On)
Max. IR LED Length	150' / 50m
Day / Night	ICR Filter Changer
OSD Menu	Support
WDR	Off / Low / Middle / High
AWB	On / Off
Defog	On / Off
Smart IR	Off / 0 ~ 16
3DNR	On / Off

Lens

Focal Length	5 ~ 60mm Motorized Megapixel Lens
Mount Type	On-board

Video

Compression	H.264 Layer 4.0, Motion JPEG
Frame Rate	H.264: 30fps @ 1920 × 1080P MJPG: 30fdps @ VGA

Audio

Connection	In: 1 (Red) Out: 1 (White)
------------	----------------------------

Network

Ethernet	RJ-45 (10 / 100Base-T)
Protocol	HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, & ICMP
Max. User Access	20
Compatibility	CGI, Onvif

General

Power Supply	DC 12V / 1.5A, PoE 802.3af
Power Consumption	Max 11W (IR On)
Working Temperature	-40°F ~ 122°F / -40°C ~ 50°C
Storage Temperature	-40°F ~ 140°F / -40°C ~ 60°C
Ingress Protection	IP67
Factory Reset	Physical button
Storage	1 Micro SD card slot
Mount	3-Axis
Dimensions (W × D × H)	4.11" × 5.41" × 13.12" / 104.3mm × 137.3mm × 333.3mm
Weight	5.73lbs / 2.6kg



Check Out Our Mobile App Lineup

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com

