

ICHD-2000P20X

1080P (Full HD over coax) HD-SDI / HDcctv 20x Optical PTZ

- Standard HD-SDI high definition digital interface (SMPT292/259)
- Day/Night (ICR), Auto iris, Auto focus, AWB, BLC
- ICR-SD Protocol with Intelligent Box Control and easy OSD Setup and also Pelco-P/D compatible
- Up to 24 privacy masking areas
- Up to 255 presets, 5 auto scans, 8 tours, 5 patterns
- Time Task: Auto activation of Preset/Scan/Tour/ Pattern by preset-time
- Idle Motion: Call Preset/Scan/Tour/ Pattern after specified time
- Auto restore to previous PTZ and lens status after power failure
- Max 400 °/s pan speed, 360° continuous pan rotation & auto flip
- Build-in 7/2 channel alarm input/output
- IP67 Weather proof with built-in temperature control
- Quick-installation Design

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

ICHD-2000P20X

1080P (Full HD over coax) HD-SDI / HDcctv 20x Optical PTZ

Model	ICIP-P3020HDIR
Camera	
Color	White
Image Sensor	HD-SDI PTZ
TVL	1/2.8" progressive scan Exmor CMOS
Lens	2 MegaPixel / 1080P
Day / Night	20x optical zoom (f=4.7mm(Wide)~94.0mm(Tele), F1.6~F3.5) / 12x digital zoom
DNR	TDN (ICR)
IP Rating	IP67
Bracket Supplied	No
Auto Rotation	Tilt 92° auto rotates to pan 180 °
Manual Pan Motion Speed	0.1°—300°/S
Preset Maximum Speed	400°
Decoder	Built-in
S/N Ratio	> 50dB
Auto Rotation	Tilt 92° auto rotates to pan 180 °
Auto Pan	0 ° -360° continuously
Power	24VAC
Power Consumption	3A (±10%)
Camera Driver Consumption	15W / 40w (Outdoor heater is on)
Dimensions	8.74" (Φ) x 12.68" (H)
	222mm (Φ) x 322mm (H)
Weight (approx)	11.02lb or 5.0kg or 176.40oz