

# ICIP-360L6

## 6 Megapixel 360° Indoor/Outdoor IR Network Dome Camera

---



A 6.0 Megapixel 360° Indoor/Outdoor Dome camera with a built in microphone. The ICIP360L6 series camera is a realtime, 360° situational awareness camera. It is capable of recording a wide area of surveillance, and de-warping the native FishEye view in order to watch a stream that is undistorted to the human eye.

### Features

- IR Max 30 Ft.
- IP66
- Built in Microphone
- PoE
- IC720 Platform Compatible



# ICIP-360L6

## Specifications

|                          |                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------|
| <b>Model</b>             | ICIP-360L6                                                                             |
| <b>Camera</b>            |                                                                                        |
| Image Sensor             | 1/8" 6 Megapixel CMOS                                                                  |
| Effective Pixels         | 3072(H)×2048(V)                                                                        |
| Scanning System          | Progressive                                                                            |
| Electronic Shutter Speed | Auto/Manual 1/4~1/10000                                                                |
| Min. Illumination        | Color: 0. 1LUX/F2.0                                                                    |
| S/N Ratio                | >52dB                                                                                  |
| <b>Camera Features</b>   |                                                                                        |
| Day/Night                | Electromagnetic type IR-CUT, Support day/night mode switch                             |
| Backlight Compensation   | BLC                                                                                    |
| White Balance            | Auto / Manual                                                                          |
| Gain Control             | Auto / Manual                                                                          |
| Noise Reduction          | 3D                                                                                     |
| Privacy Masking          | Up to 4 areas                                                                          |
| <b>Lens</b>              |                                                                                        |
| Focal Length             | 1.55mm                                                                                 |
| Max Aperture             | F2.0                                                                                   |
| Angle of View            | 185°/185°/185°                                                                         |
| Mount Type               | Wall-mount, In-ceiling and bracket                                                     |
| <b>Video</b>             |                                                                                        |
| Compression              | H.264 / H.264H / H.264B                                                                |
| Resolution               | 3072*2048 26FPS 2048*2048 26FPS 2048*1536 26FPS 1600*1200 30FPS                        |
| Frame Rate Main Stream   | 3072*2048@25fps                                                                        |
| Frame Rate Sub Stream    | 704*576@25fps                                                                          |
| Bit Rate                 | H.264: 24K ~ 12288Kbps, MJPEG: 64K ~ 65536 Kbps                                        |
| <b>Audio</b>             |                                                                                        |
| Microphone               | Built in                                                                               |
| <b>Network</b>           |                                                                                        |
| Ethernet                 | RJ-45 (10/100/1000 Base-T)                                                             |
| Protocol                 | HTTP,TCP,ARP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP,DNS,DDNS, PPPoE,IPv4/v6,SNMP,QoS,UPnP,NTP |
| ONVIF                    | ONVIF Profile S                                                                        |
| Max. User Access         | 10 users                                                                               |
| Smart Phone              | iPhone, iPad, Android, Windows Phone                                                   |
| <b>General</b>           |                                                                                        |
| Power Supply             | 12VDC, PoE(802.3af)                                                                    |
| Memory Slot              | Micro SD                                                                               |
| Power Consumption        | <11W                                                                                   |
| Working Environment      | -40°F ~ 140°F, Humidity=95%                                                            |
| Dimensions (D×H)         | F5.9"×1.88"                                                                            |
| Weight                   | 2lb                                                                                    |
| Protection               | IK10, IP66                                                                             |

# ICIP-360L12

---

## Optional Accessories



[MNT-ARM-MPB300S](#)



[MNT-BOX-MPA120](#)



[MNT-CEILING-MPA](#)



[MNT-PCNRIP](#)



[MNT-DVIR-MPA100](#)



[MNT-POLIP](#)