

ICIP-1300

1.3 Megapixel Indoor/Outdoor, Mini Bullet IR Network Camera

Affordable, yet small form factor, day/night IR bullet camera- the B1300. This sleek bullet design contains a high resolution, 1.3 Megapixel Aptina CMOS sensor, capable of outputting a crisp, clear image. The optics on this camera include a fixed 3.6mm lens. This camera is IP 66 rated and highly weatherproof. This camera is fully accessible via the entire ICR software suite, and is also compatible with third party ONVIF recorders and streamers. **UL 60950 Certified**



FEATURES

- DC12V power supply, POE
- IP66 Waterproof protection
- Dual encoding streams supported
- 1/3" 1.3 Megapixel Aptina CMOS image sensor
- 30fps @ 720P resolution, 15fps @ 1.3M(1280x960)
- H.264E video compression and JPEG image capture
- **UL 60950 CERTIFIED**

Revision: 1.0; Nov, 2016

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com



SPECIFICATIONS

Camera	
Image Sensor	1/3" 1.3Megapixel progressive scan CMOS
Effective Pixels	1280 (H)×960 (V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual; 1/3(4)s ~ 1/10,000s
Min. Illumination	0.01Lux@F1.8 (Color); 0.005Lux@F1.8 (B/W)
S/N Ratio	> 50dB

Camera Features	
Max IR LED Length	90'/30m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 Areas

Lens	
Focal Length	3.6mm
Max Aperture	F1.8
Focus Control	Manual
Angle of View	70°
Lens Type	Fixed Lens
Mount Type	Board-in Type

Video	
Compression	H.264 / MJPEG
Resolution	1.3M (1280×960) / 720P (1280×720) / D1 (704×576 / 704×480) / CIF (352×288 / 352×240)
Frame Rate	Main Stream: 1.3M / 720P (1 ~ 30fps) Sub Stream: D1 / CIF (1 ~ 30fps)
Bit Rate	H.264: 32K ~ 8192Kbps

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4 / IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, & Bonjour
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20
Smart Phone	Android, iOS, & Windows Phone

General	
Power Supply	DC12V, PoE(802.3af)
Power Consumption	Max 5W
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C, < 95% RH
Ingress Protection	IP66
Dimensions	2.75"×2.6"×6.3"/70mm×66mm×160mm
Weight	0.92lbs./0.42kg



Check Out Our Mobile App Lineup

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009
www.icrealtime.com

