

ICIP-B2000S

2 Megapixel Indoor/Outdoor, Mini Bullet IR Network Camera



Affordable, small form factor, day/night IR bullet camera – the ICIP-B2000S. This sleek bullet design contains a high resolution, 2 Megapixel Sony Progressive Scan Exmor CMOS sensor, capable of outputting a crisp, clear image. The optics on this camera include a fixed 3.6mm lens. This camera is IP 66, and highly weatherproof.

Features

- 3.6mm fixed lens
- Max. IR LEDs Length 90'
- IP66, PoE
- UL Listed 60950



ICIP-B2000S

Specifications

Model	ICIP-B2000S
Camera	
Image Sensor	1/2.8" 2Megapixel progressive scan Exmor CMOS
Effective Pixels	1920(H)×1080(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4) ~ 1/10000s
Min. Illumination	0. 1Lux@F1.6 (Color); 0.01Lux@F1.6(B/W); 0Lux@F1.6(IR on)
S/N Ratio	>50dB
Camera Features	
Max IR LEDs Length	90'/30m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F1.8
Angle of View	H:88°
Lens Type	Fixed lens
Mount Type	Board-in Type
Video	
Compression	H.264 / MJPEG
Resolution	1080P (1920×1080) / 720P (1280×720) / D1 (704×480) / CIF (352×240)
Frame Rate	Main Stream: 1080P/720P (1 ~ 25/30fps) Sub Stream: D1/CIF (1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20
Smart Phone	iPhone, iPad, Android, Windows Phone
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	Max 5.5W
Working Environment	-4°F ~ 140°F/-20°C ~ 60°C, Less than 95% RH
Ingress Protection	IP66
Dimensions	2.5"×6.3"/63.5mm×160mm
Weight	0.88lb/0.4kg

ICIP-B2000S

Accessories



[MNT-JUNCTION BOX 4](#)



[MNT-PCNRIP](#)



[MNT-POLIP](#)