

ICIP-BW210

2 MP Indoor/Outdoor, Small WiFi Network IR Bullet Camera



When you need a discreet camera that can stream video via WiFi the ICIP-BW210 fits the bill. With a bullet style housing and wide angle 3.6mm fixed lens this camera captures wide video scenes in 72 degrees of stunning 2MP video. Also, the ICIP-BW210 comes loaded with advanced features you would expect from a more expensive unit. The camera comes standard with digital wide dynamic range, up to 90 ft. of IR in 0 light, and 2D noise reduction. This camera can be connected to a 12V power source and setup in minutes. Discover the ease of setup our WiFi cameras offer and see how convenient surveillance becomes when the power of wireless video is at your fingertips.

Features

- 1/3" 2Megapixel progressive scan CMOS
- Max 25/30fps@1080P (1920×1080)
- 3.6mm fixed lens
- Max. IR LEDs Length 90'/30m
- Wi-Fi support
- IP66 , DC12V

ICIP-BW210

Specifications

Model	ICIP-BW210
Camera	
Image Sensor	1/3" 2 Megapixel CMOS
Effective Pixels	2048(H)×1536(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 ~ 1/10000
Min. Illumination	Color: 0.1Lux@F1.6; 0Lux@F1.6 (IR on)
S/N Ratio	>50dB
Camera Features	
Max IR LEDs Length	90'/30m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F1.8
Focus Control	Manual
Angle of View	H:72°
Lens Type	Fixed
Mount Type	Board-in Type
Video	
Compression	H.264H / H.264B / H.264 / MJPEG
Resolution	1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) / CIF (352×288/352×240)
Frame Rate	Main Stream: 1080P (1 ~ 25/30fps) Sub Stream: D1/CIF (1 ~ 25/30fps)
Bit Rate	H.264: 56K ~ 8192Kbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	802.11b/g/n
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
General	
Power Supply	12VDC
Power Consumption	< 7W
Working Environment	-22°F ~ 122°F/-30°C ~ 50°C; Less than 95%RH
Ingress Protection	IP66
Dimensions	Φ2.8"×2.6"×6.1"/Φ70mm×66mm×155mm
Weight	0.93lb/0.42kg

ICIP-BW210

Accessories



[MNT-PCNRIP](#)



[MNT-POLIP](#)