

ICIP-D1300-2.8

1.3 Megapixel Indoor/Outdoor, Low Profile Network Dome Camera

This camera is an extreme, low-profile, near flush-mount, IP dome camera. Inside, it contains a high resolution 1.3 MP image sensor, capable of outputting a crisp, clear image. The optics on this camera include a fixed, 2.8mm lens, providing a wide field of vision. This camera supports PoE, is fully accessible via the entire ICR software suite, and is also compatible with third-party ONVIF equipment.



FEATURES

- 2.8mm fixed lens
- 30fps @ 720P resolution
- IP67, PoE
- Max IR LED 60'/20m

Revision: 1.1; November 2016

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009
www.icrealtime.com



SPECIFICATIONS

Camera	
Image Sensor	1/3" 1.3Megapixel progressive scan CMOS
Effective Pixels	1280 (H)×960 (V)
Scanning System	Progressive
Electronic Shutter Speed	Auto / Manual, 1/3(4)s ~ 1/10,000s
Min. Illumination	0.01Lux@F1.8 (color); 0Lux@F1.8 (IR on)
S/N Ratio	> 50dB

Camera Features	
Max IR LED Length	60'/20m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Sunny / Night / Outdoor / Customized
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas

Lens	
Focal Length	2.8mm
Max Aperture	F1.8
Focus Control	Manual
Angle of View	H: 86°
Lens Type	Fixed
Mount Type	Board-in

Video	
Compression	H.264 / H.264B / H.264H / MJPEG
Resolution	720P (1280×720) / D1 (704×576 /

	2×288 / 352×240)
Frame Rate	Main Stream: 1.3M / 720P(1 ~ 30fps) Sub Stream: D1 / CIF(1 ~ 30fps) Third Stream: 720P (1-7fps)
Bit Rate	H.264: 32K ~ 10Mbps
Corridor Mode	Support

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4 / IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, & 802.1x
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20
Smart Phone	Android, iOS, & Windows

General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	< 5W
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C; < 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10
Dimensions	Φ4.2"×2.0"/Φ106mm×50.3mm
Weight	0.77lbs/0.35kg



Check Out Our Mobile App Lineup

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com

