

## ICIP-D1300AIR

### 1.3Megapixel HD Network Small IR Dome Camera

- 1/3" 1.3Megapixel progressive scan Aptina CMOS
- H.264&MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280x960) & 720P(1280x720)
- DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- Multiple network monitoring: Web viewer, CMS(SmartICRSS/PSS) & ICRSS Pro
- 2.8mm fixed lens
- Max. IR LEDs Length 65"

## Product Overview



#### Head Office

IC Realtime  
3050 N Andrews Ave AXE  
Pompano Beach,  
FL 33064

Tel: 1 (866) 997-9009  
Fax: 1 (954) 827-5900  
Email: [Info@icrealtime.com](mailto:Info@icrealtime.com)  
Web: [www.icrealtime.com](http://www.icrealtime.com)

#### West Coast Office

IC Realtime  
14180 West Van Buren St.  
Suite B105  
Goodyear, AZ 85338

Tel: 1 (602) 910-3432  
Fax: 1 (602) 626 3545  
Email: [west@icrealtime.com](mailto:west@icrealtime.com)  
Web: [www.icrealtime.com](http://www.icrealtime.com)

## ICIP-D1300AIR

### 1.3Megapixel HD Network Small IR Dome Camera

|                          |                                                                        |                                   |
|--------------------------|------------------------------------------------------------------------|-----------------------------------|
| Model                    | ICIPD1300AIR                                                           |                                   |
| Camera                   |                                                                        |                                   |
| Image Sensor             | 1/3" 1.3Megapixel Aptina CMOS                                          |                                   |
| Effective Pixels         | 1280(H) ´ 960(V)                                                       |                                   |
| Scanning System          | Progressive                                                            |                                   |
| Electronic Shutter Speed | Auto/Manual, 1/4~1/10000s                                              |                                   |
| Min. Illumination        | 0. 01Lux/F1.2 (Color), 0.005Lux/F1.2(B/W);0Lux/F1.2(IR on)             |                                   |
| S/N Ratio                | More than 50dB                                                         |                                   |
| Camera Features          |                                                                        |                                   |
| Max. IR LEDs Length      | 60'                                                                    |                                   |
| Day/Night                | Auto(ICR)/Color/B/W                                                    |                                   |
| Backlight Compensation   | BLC / HLC / DWDR                                                       |                                   |
| White Balance            | Auto/Manual                                                            |                                   |
| Gain Control             | Auto/Manual                                                            |                                   |
| Noise Reduction          | 3D                                                                     |                                   |
| Privacy Masking          | Up to 4 areas                                                          |                                   |
| Lens                     |                                                                        |                                   |
| Focal Length             | 2.8mm                                                                  |                                   |
| Max Aperture             | F1.6                                                                   |                                   |
| Focus Control            | Manual                                                                 |                                   |
| Angle of View            | H: 70°(114°/46°)                                                       |                                   |
| Lens Type                | Fixed lens                                                             |                                   |
| Mount Type               | Board-in Type                                                          |                                   |
| Video                    |                                                                        |                                   |
| Compression              | H.264/ MJPEG                                                           |                                   |
| Resolution               | 1.3M(1280x960)/720P(1280x720)/D1(704x576)/CIF(352x288)                 |                                   |
| Frame Rate               | 1.3M(1~15fps)/720P(1 ~ 25/30fps)                                       | Sub Stream: H.264: 32K ~ 8192Kbps |
| Bit Rate                 | H.264: 32K ~ 8192Kbps                                                  |                                   |
| Network                  |                                                                        |                                   |
| Ethernet                 | RJ-45 (10/100Base-T)                                                   |                                   |
| Protocol                 | Pv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, |                                   |
| ONVIF                    | ONVIF Profile S                                                        |                                   |
| Max. User Access         | 20 users                                                               |                                   |
| Smart Phone              | iPhone, iPad, Android, Windows Phone                                   |                                   |
| General                  |                                                                        |                                   |
| Power Supply             | DC12V, PoE (802.3af)                                                   |                                   |
| Power Consumption        | <5W                                                                    |                                   |
| Working Environment      | -14°F - 122° F (-25°C - 50° C) 90% RH                                  |                                   |

|                    |             |
|--------------------|-------------|
| Ingress Protection | IP66        |
| Vandal Resistance  | N/A         |
| Dimensions         | Φ114mmx86mm |
| Weight             | 0.4kg       |