ICIP-D2000VIR-B

2 Megapixel Indoor/Outdoor, Full-Size IR Dome IP Camera

A rugged, day/night, outdoor rated 2 Megapixel IP dome camera with an automatic motorized lens – the ICIP-D2000VIR-B. Featuring a hardened dome chassis, the ICIP-D2000VIR-B is IK10 impact resistant, and IP66 weatherproof, making it well suited as a vandal resistant camera. Contained inside is a high resolution 2 Megapixel Aptina CMOS imager, capable of outputting a crystal clear image. The optics include a vari-focal 3~9mm motorized varifocal lens. IR LEDs on this unit are suitable for viewing up to 60’ with 0 light.

Features

- 3~9mm varifocal automatic motorized lens
- Max. IR LEDs length 60FT
- IP66 Weatherproof, IK10 Vandalproof
- Micro SD memory
- Built-in 2/1 alarm in/out
- UL Listed 60950
- Also available in white: ICIP-D2000VIR; and black with tinted dome cover: ICIP-D2000VIR-B-D

ICIP-D2000VIR-B

Specifications

Model	ICIP-D2000VIR-B
Camera	
Image Sensor	1/2.8” 2Megapixel progressive scan Exmor CMOS
Effective Pixels	1920(H)x1080(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual 1/4~1/10000
Min. Illumination	0.1lux/F1.4(color), 0Lux/F1.4(IR on)
S/N Ratio	>50dB
Video Output	1 port
Camera Features	
Max IR LEDs Length	60Ft 20m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3-9mm motorized
Max Aperture	F1.2
Focus Control	Auto
Angle of View	H: 103.9°(Wide)~34.1°(Tele)
Lens Type	Motorized /Auto Iris(DC)
Mount Type	Board-in Type
Video	
Compression	H.264/MJPEG
Resolution	1080P(1920×1080) /720P(1280×720) / D1(704×480) / CIF(352×240)
Frame Rate	Main Stream: 1080P/720P(1 ~ 25/30fps) Extra / Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps
Audio	
Compression	G.711a /G.711u /PCM
Interface	1/1 channel In/Out
Network	
Ethernet	RJ-45 (10/100Base-T)
WiFi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, CGI
Max. User Access	20
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 64GB

Alarm	1/1 channel In/Out
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<8.5W
Working Environment	-20°C ~ 60°C/-4°F ~ 140°F, Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ5.94"x4.68"mm ~ Φ151mmx119mm
Weight	3.3lb/1.25kg

Optional Accessories

MNT-ARM-MPB300S

MNT-BOX-MPA120

MNT-DVIR-MPA100

MNT-PCNRIP-B

MNT-POLIP

IC Realtime LLC
3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009
www.icrealtime.com
Designs and specifications subject to change without notice. Copyright © 2015 IC Realtime, LLC. All rights reserved.