

ICIP-D2000VIR-B-D

2 MP Indoor/Outdoor, Vandal proof Full-Size IR Dome IP Camera



A rugged, day/night, outdoor-rated 2 Megapixel IP dome camera with an automatic motorized lens – the ICIP-D2000VIR-B-D. Featuring a hardened dome chassis, the ICIP-D2000VIR-B-D is IK10 impact resistant, and IP66 weatherproof, making it well suited as a vandal resistant camera. Contained inside is a high resolution 2 Megapixel Aptina CMOS imager, capable of outputting a crystal-clear image. The optics include a varifocal 3~9mm motorized lens. IR LEDs on this unit are suitable for viewing up to 60' with 0 light.

Features

- 3 ~ 9mm varifocal automatic motorized lens
- Max. IR LEDs length 60'/20m
- IP66, IK10 Weatherproof, & Vandal proof
- Micro SD Memory
- Built-in 2/1 alarm in/out
- UL Listed 60950
- Also available in White: [ICIP-D2000VIR](#) and with a clear dome: [ICIP-D2000VIR-B](#)

ICIP-D2000VIR-B-D

Specifications

Model	ICIP-D2000VIR-B-D
Camera	
Image Sensor	1/2.8" 2MP progressive scan Exmor CMOS
Effective Pixels	1920 (H)×1080 (V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual 1/4 ~ 1/10000
Min. Illumination	0.1lux@F1.4 (color); 0Lux@F1.4 (IR on)
S/N Ratio	> 50dB
Video Output	1 port
Camera Features	
Max IR LEDs Length	60' / 20m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3 - 9mm motorized
Max Aperture	F1.2
Focus Control	Auto
Angle of View	H: 103.9°(W) ~ 34.1° (T)
Lens Type	Motorized / Auto Iris (DC)
Mount Type	Board-in Type
Video	
Compression	H.264 / MJPEG
Resolution	1080P (1920×1080) / 720P (1280×720) / D1 (704×480) / CIF (352×240)
Frame Rate	Main Stream: 1080P / 720P (1 ~ 30fps) Extra / Sub Stream: D1 / CIF (1 ~ 30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps
Audio	
Compression	G.711a / G.711u / PCM
Interface	1/1 channel In / Out
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, CGI
Max. User Access	20
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 64GB
Alarm	1/1 channel In/Out
General	
Power Supply	DC12V, PoE (802.3af)

Power Consumption	< 8.5W
Working Environment	-4°F ~ 140°F/-20°C ~ 60°C; Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ5.94"×4.68"mm/Φ151mm×119mm
Weight	3.3lb/1.25kg

Accessories



[MNT-ARM-MPB300S](#)



[MNT-BOX-MPA120](#)



[MNT-DVIR-MPA100](#)



[MNT-PCNRIP-B](#)



[MNT-POLIP](#)