

ICIP-D2010-IR-D

2 Megapixel Indoor/Outdoor, Mini IR Tinted Dome IP Camera



This camera is a low profile, near flush mount 2MP IP Indoor-Outdoor Vandal IR dome camera. Inside it contains a high resolution, 2 Megapixel Progressive Scan Exmor CMOS sensor, capable of outputting a crisp and clear image. The optics on this camera include a fixed 3.6mm lens, providing a rather wide field of vision. Built in IR LED illumination is effective up to 90' at 0 light. The ICIPD2010IR is IP-66 and IK10 rated.

Features

- 3.6mm fixed lens
- Max. IR LEDs Length 30m
- IP66, IK10, PoE
- 30fps@1080P(1920x1080)


ICIP-D2010-IR-D

Specifications

Model	ICIP-D2010-IR-D (Tinted Dome)
Camera	
Image Sensor	1/2.8" 2Megapixel progressive scan Exmor CMOS
Effective Pixels	1920(H)x1080(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
Min. Illumination	0. 1Lux/F1.8 (Color), 0.01Lux/F1.8(B/W)
S/N Ratio	>50dB
Video Output	N/A
Camera Features	
Max IR LEDs Length	90ft / 30m
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F1.8
Focus Control	Manual
Angle of View	H:88°
Lens Type	Fixed lens
Mount Type	Board-in Type
Video	
Compression	H.264/MJPEG
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Frame Rate	Main Stream - 1080P/720P(1 ~ 25/30fps) Sub Stream - D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps
Audio	
Compression	N/A
Interface	N/A
Network	
Ethernet	RJ-45 (10/100Base-T)
WiFi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF,PSIA,CGI
Max. User Access	20
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	N/A

RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	Max 4W
Working Environment	-4°F~+140°F, -30°C~+60°C, Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ 4.33" x 3.19" Φ110mm×81mm
Weight	0.64lb 0.29kg

Optional Accessories



[MNT-IPMINIDOME-WALL](#)



[MNT-JUNCTION BOX 2](#)



[MNT-PCNRIP](#)



[MNT-POLIP](#)