

ICIP-D3077P

3 MP Indoor/Outdoor, Vandalproof Mini P/T IP Dome Camera



The ICIP D3077P is a high resolution 3MP robotic point dome camera with a super low profile (no zoom). The 3 Megapixel Progressive Scan CMOS sensor and included 3.6mm fixed lens output a crisp and clear image with a rather wide field of vision. The ICIP D3077P is an indoor / outdoor camera with an IP-66 and IK10 rating. This camera supports PoE, is fully accessible via the entire ICR software suite, and is also ONVIF compatible.

Features

- 3.6mm fixed lens
- 1/3" 3Megapixel progressive scan CMOS
- IP66, IK10
- Max 100°/s preset speed, $\pm 180^\circ$ Pan range, 90° Tilt range
- Max 20fps@3M(2048 $\times$ 1536), 25/30fps@1080P

ICIP-D3077P

Specifications

Model	ICIP-D3077P
Camera	
Image Sensor	1/3" 3Megapixel progressive scan CMOS
Effective Pixels	2048(H)×1536(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto / Manual 1/3~1/10000
Min. Illumination	0.01lux / F1.2(color)
S/N Ratio	>50dB
Camera Features	
Day/Night	Auto (Electronic) / Color / B/W
Backlight Compensation	Off / BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Digital Zoom	3x
Lens	
Focal Length	3.6mm
Max Aperture	F1.2
Focus Control	Manual
Angle of View	H:72.5°
Lens Type	Fixed lens
Mount Type	Board-in Type
PT	
Pan/Tilt Range	Pan: 0°~±180°; Tilt: 0°~90°
Preset Speed	100°/s
Preset	25
Video	
Compression	H.264/MJPEG
Resolution	3.0M(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Frame Rate	Main Stream: 3M(1~20fps)/1080P/720P(1 ~ 25/30fps) Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps
Audio	
Compression	G.711a / G.711u / PCM
Interface	Built-in Mic
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Profile S
Max. User Access	20
Smart Phone	iPhone, iPad, Android, Windows Phone

Auxiliary Interface	
Memory Slot	Micro SD, Max 64GB
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	Max 3W
Working Environment	-20°C ~ 60°C, Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ5.12"×2.26"
Weight	0.55lb

Optional Accessories



[MNT-IPMINIDOME-WALL](#)



[MNT-JUNCTION BOX 2](#)