

ICIP-DW212

2 MP Indoor/Outdoor, Vandal Mini WiFi Network Dome Camera



You asked for WiFi Cameras and we delivered. Throw away the CAT-5 and enter the world of easy installations and wireless nirvana. Enter the ICIP-DW212, a 2MP wireless dome camera with all the bells and whistles you have come to expect. This camera features Day/Night capability with a robust IR beam out to 100 feet of nighttime viewing. It has many extras like digital wide dynamic range, backlight compensation, and noise reduction. The camera runs on 12V and is IP66 rated which means it can handle heavy seas and dust storms.

Features

- 1/3" 2 Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Max 30fps@720P (1280×720)
- DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web browsers, SmartICRSS, ICRSS Pro, & ICVIEW
- 3.6mm fixed lens
- Wi-Fi support
- DC12V

ICIP-DW212

Specifications

Model	ICIP-DW212
Camera	
Image Sensor	1/3" 2 Megapixel CMOS
Effective Pixels	2048(H)×1536(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 ~ 1/10000
Min. Illumination	Color: 0.1Lux@F1.8; 0Lux@F1.8 (IR on)
S/N Ratio	>50dB
Camera Features	
Max IR LEDs Length	100'/30m
Day/Night	Auto (Electronic) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F1.8
Focus Control	Manual
Angle of View	H:71.9°
Lens Type	Fixed
Mount Type	Board-in Type
Video	
Compression	H.264 / MJPEG
Resolution	1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) / CIF (352×288/352×240)
Frame Rate	Main Stream: 1080P (1 ~ 25/30fps) Sub Stream: D1/CIF (1 ~ 25/30fps)
Bit Rate	H.264: 56K ~ 8192Kbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	802.11b/g/n
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
General	
Power Supply	12VDC
Power Consumption	< 4.5W
Working Environment	-22°F ~ 122°F/-30°C ~ 50°C; Less than 95%RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ4.33"×3.19"/Φ110mm×81mm
Weight	0.86lb/0.39kg

ICIP-DW212

Accessories



[MNT-IPMINIDOME-WALL](#)



[MNT-JUNCTION BOX 2](#)



[MNT-PCNRIP](#)



[MNT-POLIP](#)