

ICIP-T801-I

1.3 MP Intelligent Pinhole Network Camera



Features

- 1/3" 1.3Megapixel progressive scan CMOS
- Max 30fps@1.3MP (1280×960)
- Day/Night (Electronic), 3DNR, AWB, AGC, & BLC
- Smart detection: Face, Tripwire, Intrusion, & Scene change detection
- 3.6mm fixed lens
- Micro SD memory, PoE

ICIP-T801-I

Specifications

Model	ICIP-T801-I
Camera	
Image Sensor	1/3" 1.3Megapixel progressive scan CMOS
Effective Pixels	1280(H)×960(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto / Manual; 1/4sec ~ 1/100,000sec
Min. Illumination	0.01Lux@F2.8 (Color); 0.001Lux@F2.8 (B/W)
S/N Ratio	> 50dB
Features	
Day/Night	Auto (Electronic) / Color / B/W
Backlight Compensation	BLC / HLC / WDR (100dB)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F2.8
Focus Control	Manual
Angle of View	H: 77°
Lens Type	Fixed
Mount Type	Board-in Type
Video	
Compression	H.264 / MJPEG
Resolution	1.3M (1280×960) / 720P (1280×720) / D1 (704×576) / CIF (352×288)
Frame Rate	Main Stream: 1.3M / 720P (1 ~ 30fps) Sub Stream: D1 / CIF (1 ~ 30fps) Third Stream: 720P / D1 / CIF (1 ~ 30fps)
Bit Rate	H.264: 48K ~ 8192Kbps
Audio	
Compression	G.711a / G.711u / PCM
Interface	1/1 channel In/Out
Intelligent Functions	
Smart Detection	Tripwire, Intrusion, Scene change, Missing/Abandoned, Audio detect, Face detect
Network	
Ethernet	RJ-45 (10/100/1000Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, & Bonjour
Compatibility	ONVIF, PSIA, & CGI
Max. User Access	20
Smart Phone	iPhone, iPad, Android, & Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 64GB
Alarm	1/1 channel In/Out

General	
Power Supply	12V DC, PoE (802.3af)
Power Consumption	Max 7W
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C; < 95% RH
Dimensions	4.32"×3.26"×0.94"/109.7mm×82.8mm×24mm
Weight	1.01lbs/0.46kg