

IH-C6260

1 Megapixel Advanced Network Intercom System



Outdoor intercom station designed to work with our indoor monitors. The camera is equipped with a 1.3 Megapixel CMOS chipset, and a crystal clear two-way audio microphone plus speaker. This camera requires the use of IH-D7210, IH-D7710Z, or IH-D7711Z to function as intended.

Features

- 1.3 MP CMOS Camera
- Easy to operate, just one illuminated button
- Remote unlock
- Group call
- Two-way audio
- Push Notification direct to mobile devices

IH-C6260

Specifications

Model	IH-C6260
System	
Main Processor	Embedded micro processor
Operating System	Embedded LINUX OS
Video	
Video Compression Standard	H.264
Input/Approaching Induction	1.3MP CMOS HD camera
Black Light	Support
Audio	
Audio Input	Omnidirectional Microphone
Audio Output	Built-in loudspeaker
Bi-directional Talk	Support bi-directional talk
Input	
Operation Mode	One-key input (with blacking)
Alarm & Access Control	
Vandal Proof	H.264/ MJPEG
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
Storage	
Memory	128MB
General	
Power Supply	DC 10~15V
Power Consumption	Standby ≤1W, work ≤10W
Working Environment	14°F ~ 130°F/-10°C ~ 55°C / 10~90%RH / 86~106kpa
Dimensions (W×D×H)	5.6"×3.9"×0.7"
Weight	1.76lb/0.8kg

IC Realtime LLC
3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009
www.icrealtime.com

Designs and specifications subject to change without notice. Copyright © 2015 IC Realtime, LLC. All rights reserved