

MAIP-D2360-S

2 MP Marine 360° Network Dome Camera

2.0 MP 360° marine dome camera with a built-in microphone. The MAIP-D2360 series cameras are real-time, 360° situational awareness units. They are capable of recording wide areas all at once. The images can be de-warped from the native FishEye view, producing a stream that is undistorted to the human eye.



FEATURES

- 1/3" 2MP Exmor CMOS
- ONVIF Profile S
- PoE (802.3af)
- Micro SD

Revision: 1.0; September 2017

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com



SPECIFICATIONS

Camera	
Image Sensor	1/3" 2 MP Exmor CMOS
Effective Pixels	1920(H) × 1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto / Manual, 1/4~1/10,000s
Minimum Illumination	0.1Lux @ F1.4 Color
S/N Ratio	< 50dB

Features	
Day / Night	Auto (Electronic) / Color / B/W
Backlight Compensation	BLC
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas

Lens	
Focal Length	1.25mm
Max. Aperture	F1.8
Angle Of View	H:180°, ±5°
Mount Type	Board-in

Video	
Compression	H.264 / MJPEG
Resolution	1080P (1920×1080) / SXGA (1280×1024) / 720P (1280×720) / D1 (704×480) / CIF

	(352×240)
Frame Rate	Main Stream: 1080P / SXGA / 720P (1 ~ 30fps) Sub Stream: D1 / CIF (1 ~ 30fps)
Bit Rate	H.264: 32K ~ 8192Kbps MJPEG: 32K ~ 12288Kbps

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, & Bonjour
ONVIF	Profile S
Max User Access	10
Smart Phone	Android, iOS, & Windows

General	
Power Supply	12VDC, PoE (802.3af)
Memory Slot	Micro SD
Power Consumption	< 2.5W
Working Environment	14°C ~ 140°F / -10°C ~ 60°C, 10% ~ 90%
Dimensions	Φ4.5"×4.5" / Φ114.3mm×114.3mm
Weight	0.55lbs / 0.25kg



Check Out Our Mobile App Lineup

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com

