

NVR-708MP

8 Channel 1.5U 8 PoE Network Video Recorder



Powerful network surveillance meets plug-and-play functionality. The 708MP series of Network Video Recorders is the top-of-the-line recorder for those who are looking for high resolution recording and built in PoE switches. The NVR708MP has 8 channels of recording capability and 1 dedicated PoE port per channel up to 8 PoE ports , and can manage 160Mbps of total decoding and recording throughput.

Features

- 8 Channels of IP Recording
- Built in 8 Port PoE Switch
- Supports 3 MP and 5 MP Cameras
- 4 SATA ports (4TB per HD)

NVR-708MP

Specifications

Model	NVR-708MP
System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Audio & Video	
IP Camera Input	8
Two-way Talk	1 channel input, 1 channel output RCA
Display	
Interface	1 HDMI, 1 VGA, 1 BNC
Resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Display Split	1/4/8/9
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Video Compression	H.264 / MJPEG
Image Resolution	5MP (2560x1920) / 3MP (2048x1536) / 1080P (1920x1080) / 720P (1280x720) / D1 (704x576/704x480)
Record Rate	160Mbps
Bit Rate	48~8192Kb/s
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank
Alarm Input	16 channel
Relay Output	4 channel
Playback & Backup	
Sync Playback	1/4/9
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network / eSATA
Network	
Ethernet	RJ-45 port (10/100M/1000M)
PoE	16 ports (IEEE802.3af)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server, SNMP, P2P
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	4 SATA ports
External HDD	1 eSATA port
Auxiliary Interface	
USB	2ports (1 Rear USB3.0, 1 Front USB2.0)
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control

General	
Power Supply	100~240VAC 50/60Hz
Power Consumption	NVR: 40W PoE: 25.5W per port
Working Environment	14 ~ 131° F (-10 ~ +55°C) / 10~90%RH / 86~106kpa
Dimensions (W×D×H)	1.5U, 440mm x 410mm x 70mm
Weight	6 KG (without HDD)