


32 Channel 2U Network Video Recorder

Features

- Up to 32 channel with 1080p realtime live view
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution
- Max 240fps@1080p, 480fps@720p, 960ps@D1 preview & recording
- HDMI / VGA simultaneous video output
- 16 channel synchronous realtime playback, GRID interface
- Support Multi-brand network cameras: Dahua, Arecont
- Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech and etc.
- ONVIF Version 2.0 conformance
- 3D intelligent positioning with IC Realtime PTZ camera
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Multiple network monitoring: Web viewer, CMS(PSS) & ICRSS



Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14200 W. Van Buren st Suite C-106
Goodyear
AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 623 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

NVR-732X2

Specifications

Model	NVR732X2
System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	32 channel
Two-way Talk	1 channel Input, 1 channel Output, BNC
Display	
Interface	1 HDMI, 1 VGA, 1TV
Resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Display Split	1/4/8/9/16/25/32
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Compression	H.264 / MJPEG
Resolution	5MP(2560x1920) / 3MP(2048x1536) / 1080P(1920x1080) / 720P(1280x720) / D1 (704x576/704x480)
Record Rate	Max 240fps@1080p, 480fps@720p, 960ps@D1
Bit Rate	48~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min). Pre-record: 1~30 sec. Post-record: 10~300 sec
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank
Alarm Input	16 channel
Relay Output	6 channel
Playback & Backup	
Sync Playback	1/4/8/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / eSATA Device / Internal SATA burner/ Network
Network	
Ethernet	2 RJ-45 port (10/100M/1000M)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search(Support IC Realtime IP camera, DVR, NVS and etc.)
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB
External HDD	1 eSATA port (Max 4 SATA HDDs), up to 16TB
Auxiliary Interface	
USB	4 ports (2 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	AC 100~240V, 50/60 Hz
Power Consumption	40W
Working Environment	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimension (WxDxH)	2U, 440mm x 460mm x 89mm
Weight	6KG(without HDD)

Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14200 W. Van Buren st Suite C-106
Goodyear
AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 623 3545
Email: west@icrealtime.com
Web: www.icrealtime.com