DVR-M708GCW

8 Channel Mobile NVR with 3G Cellular, GPS, and WiFi

Rugged and robust, with a vibration-dampening design, this mobile series of NVRs is specifically engineered for installation in ships, cars, trucks, and other 'rough-and-tumble' environments. The mobile NVR utilizes 2 'laptop' grade HDDs in conjunction with a vibration-dampening drive cradle, to create a rugged mobile video recording solution.

FEATURES

- → 1080P @ 30fps
- → 2 SATA HDDs, 2 USB
- → 1 RJ-45 port (10/100M/1000M)
- → Built-in GPS, 3G Cellular, & WiFi

Revision: 1.0; July 2017

IC Realtime LLC
3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009
www.icrealtime.com

Designs and specifications subject to change without notice. Copyright © 2015 IC Realtime, LLC. All rights reserved.

SPECIFICATIONS

System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX

Video	
Input	8 channel
Standard	NTSC, PAL

Audio	
Input	8 channel
Output	1 channel
Two-way Talk	1 channel Input, 1 channel Output (Aviation connector)

Display	
Interface	1 HDMI, 1 VGA, 2 TV
Resolution	1920×1080, 1280×1024, 1280×720, & 1024×768
Split	1 / 4 / 8 / 9
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, & Recording

Recording	
Compression	H.264 / MJPEG
Resolution	1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480)
Record Rate	200 / 240fps @ 1080P
Bit Rate	48 ~ 8192Kb/s
Mode	Manual, Schedule (Regular (Continuous), MD, Alarm), & Stop
Interval	1 ~ 120 min (default: 60 min) Pre-record: 1 ~ 30 sec Post-record: 10 ~ 300 sec

Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer, & Screen tips
Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, & Camera Blank
Alarm Input	8 channel
Relay Output	3 channel

Playback & Backup	
Sync Playback	4 / 8
Search Mode	Time / Date, Alarm, Motion Detection, & Exact search (accurate to second), & Smart Search
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, & Digital zoom
Backup Mode	USB Device / Network

Network	
Ethernet	1 RJ-45 port (10/100M/1000M)
Wireless	Built-in 3G / WiFi module
GPS	Built-in highly accurate GPS module
Functions	HTTP, IPv4, TCP/IP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, & IP Filter
Max. User Access	10

Storage	
Internal HDD	2 SATA ports

Auxiliary Interface	
USB	2 ports (1 Rear), USB2.0
RS232	1 port
RS485	1 port
eSATA	1 port
Memory Slot	SD Card, ≤ 32GB

General	
Power Supply	6V ~ 36V
Power Consumption	≤ 10W
Working Environment	14°F ~ 132°F / -10°C ~ 55°C; 10% ~ 90% RH; 86 ~ 106 kPa
Dimensions (W × D × H)	71“ × 8.2” × ”3.9 / 180mm × 208mm × 100mm
Weight	6.6lbs / 3kg (w/o HDD)

Check Out Our Mobile App Lineup

IC Realtime LLC
3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009
www.icrealtime.com

Designs and specifications subject to change without notice. Copyright © 2015 IC Realtime, LLC. All rights reserved.