

PWR-HIPOE-8

8-Port Hi-PoE Switch



Revision: 1.0; August 2017

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com



Designs and specifications subject to change without notice. Copyright © 2015 IC Realtime, LLC. All rights reserved.

SPECIFICATIONS

	System
Ethernet Ports	1 – 1,000 Base-X 1 – 10 / 100 / 1,000 Base-T 8 – 10 / 100 Base-T PoE
PoE Power Consumption	Power Supply Ports 1 & 2: 60W Hi-PoE (IC Realtime proprietary) Ports 3 & 4: 30W PoE + (802.3at) Ports 5 – 8: 15.4W PoE (802.3af) Total: 120W

PoE Protocols	IEEE802.3af & IEEE802.3at
Exchange Mode	Store & forward
Application Humidity	10% - 90%
Power	AC100 / 40V
Operating Environment	4°F ~ 131°F / -10°C ~ 55°C
Weight	5.86lbs / 2.66kg
Dimensions (W×D×H)	11.8"×8.7"×1.8" / 300mm×220mm×44.4mm



Check Out Our Mobile App Lineup

IC Realtime LLC

3050 N Andrews Avenue Extension
Pompano Beach, FL 33064
(866) 997-9009

www.icrealtime.com

